

# USED TRUE 3 DOOR REFRIGERATOR MERCHANDISER GDM-72-HC~TSL01



**Brand:** TRUE Refrigeration  
**Product Code:** USED GDM-72-HC~TSL01  
8940151  
**Availability:** In Stock  
**Weight:** 0.00kg  
**Dimensions:** 0.00cm x 0.00cm x 0.00cm

**Price: \$2,972.00**

## Short Description

TRUE 2 DOOR REFRIGERATOR MERCHANDISER GDM-72-HC~TSL01

## Description

**TRUE 3 DOOR REFRIGERATED MERCHANDISER: RETAILS NEW FOR \$6,186**

The True GDM-72-HC~TSL01 three-section glass door merchandiser holds packaged foods at safe temperatures between 33 and 38 degrees Fahrenheit. It uses glass doors and LED interior lighting to increase product visibility, raising the chance of impulse purchases. Using R290 hydrocarbon refrigerant, an environmentally friendly option, the capillary tube system keeps the product cold. Polyurethane insulation and low-E insulated glass doors keep cold air inside the cabinet.

Operating in reverse for 20 seconds after the compressor turns on, the condensing fan motor reduces dust build up on the condensing coil. Keeping the coil clean extends the unit's lifespan and increases its efficiency. To use less energy and keep stored product cool, this feature should be used alongside routine maintenance.

A bottom-mounted compressor provides accessibility to the internal components of this

glass door merchandiser for cleaning and servicing. So customers can reach products stored on the lowest shelf, the bottom of the cabinet is lifted. The True GDM-72-HC~TSL01 three-section glass door merchandiser is compliant to store and display packaged and bottled products. It has a black powder coating on the exterior that resists peeling and chipping.

## **Product Details**

- 3-door refrigerated merchandiser
- Swing-out glass doors have insulated, double-pane glass to trap cold air
- Self-closing doors help with temperature recovery
- Each door has a 12-in. handle
- Magnetic door gaskets are removable to simplify cleaning
- Black powder-coated exterior is durable and non-peeling
- Interior LED lighting helps provide product visibility
- Foamed-in-place, high-density insulation keeps cool air inside the cabinet
- 12 PVC-coated wire shelves are adjustable in 1½-in. increments
- Clean-out drain located in cabinet floor for cleaning

## **Refrigeration System**

- Temperature range: 33-38 degrees F
- Uses environmentally friendly R290 hydrocarbon refrigerant
- Bottom-mounted condensing unit raises the bottom shelf for no-stoop access and ensures components are accessible for cleaning and servicing
- Evaporator and condenser fan motors move a more consistent volume of air, producing less heat
- Dust removed from condensing coil with reverse condensing fan motor
- Epoxy-coated evaporator and powder-coated steel frame resist corrosion

## **Dimensions & Utilities**

- Shelves: 241½ in. W x 203¼ in. D
- Overall: 781½ in. W x 311¼ in. D x 785½ in. H
- 9.3 A, 1½ HP
- 115 V/60 Hz/1 ph, 9-ft. cord with a NEMA 5-15P plug

**COMES WITH 30 DAY WARRANTY - FROM TEXAS RESTAURANT EQUIPMENT**

**PRODUCT**

**SHEET:**

<https://assets.katomcdn.com/raw/upload/v1686663908/products/598/598-GDM72BK/598-GDM72BK.pdf>

**PICKUP AND FREIGHT: TO BE ARRANGED AFTER PURCHASE, ITEM IS LOCATED IN HOUSTON, TX.**

**Serial: 8940151**

**Year: 2016**

**Product Gallery**



